


Snuggli®



ALL-IN-ONE CAR SEAT

Owner's Manual
Keep for future use.



REAR-FACING

2.3 to 18 kg | 48 to 94 cm
(5 to 40 lbs) | (19 to 37 in.)



FORWARD-FACING

10 to 29.4 kg | 71 to 127 cm
(22 to 65 lbs) | (28 to 50 in.)



BOOSTER

18 to 49.8 kg | 110 to 145 cm
(40 to 110 lbs) | (43.3 to 57 in.)

Para instrucciones en Español,
llamar al: 1-800-233-5921

⚠️WARNING:

To reduce the risk of serious injury or death, read this owner's manual prior to installing and using this child restraint.

25706760 4/13
©2013 Evenflo Company, Inc.

More children are killed every year as passengers in car crashes than by any other type of injury.

To reduce the risk of **SERIOUS INJURY** or **DEATH**, read this owner's manual and your vehicle owner's manual before installing and using this child restraint. Using a child restraint makes a big difference. By properly using this child restraint and following these instructions (and the instructions that accompany your vehicle), you will greatly reduce the risk of serious injury or death to your child from a crash. Do not be misled by the commonly used term "safety seat"; no restraint system can prevent all injuries in all crashes. Many properly restrained adults and children are injured in motor vehicle crashes, including relatively minor crashes. A properly used child restraint is the best way to minimize injuries to your child and to increase the chances for your child's survival in most crashes.

U.S. REGULATORY NOTICE

This child restraint meets all applicable requirements of Federal Motor Vehicle Safety Standard 213.

**For Canadian Models
CANADIAN REGULATORY NOTICE**

This child restraint meets all applicable requirements of Canadian Motor Vehicle Safety Standards CMVSS 213, 213.1, and 213.2.

Child Requirements

- **No restraint can guarantee absolute protection from injury in every crash.**
- **This child restraint is designed for use by children in rear-facing, forward-facing, and booster modes. To use this child restraint properly, children **MUST** meet weight/size specifications as follows:**

For Rear-facing Use

- The child weighs 2.3 to 18 kg (5 to 40 lbs).
- The child is 48 to 94 cm (19 to 37 inches) **AND** the top of child's head is at least 25 mm (1 inch) **below the top** of the child restraint headrest in either of its two lowest positions.

For Forward-facing Use

- The child weighs 10 to 29.4 kg (22 to 65 lbs).
- The child is 71 to 127 cm (28 to 50 inches) **AND** the tops of their ears are below the top of the child restraint headrest.
- Child is one year old or older.

For Booster Use

- The child weighs 18 to 49.8 kg (40 to 110 lbs).
- The child is 110 to 145 cm (43.3 to 57 inches) **AND** the tops of their ears are below the top of the child restraint headrest.
- Child is four years old or older.

Table of Contents

Important Information

Warnings	2
Safe Practices	10
Recall Information for U.S. Customers	10
Public Notice for Canadian Customers	10
Motor Vehicle/Aircraft Usage.....	11
LATCH Information	11
Symbol Legend	11
Visual Glossary	12
Securing the Child	14
Removing the Child	16

Rear-facing Use

Installation Checklist	19
Moving SureLatch™ to Rear-facing Belt Path	20
Rear-facing Installation with SureLatch Connectors	22
Moving Quick Connectors™ to Rear-facing Belt Path	24
Rear-facing Installation with Quick Connectors	26
Rear-facing Installation with the Seat Belt.....	28

Forward-facing Use

Installation Checklist	33
Moving SureLatch to Forward-facing Belt Path.....	34
Forward-facing Installation with SureLatch Connectors	36
Moving Quick Connectors to Forward-facing Belt Path.....	40
Forward-facing Installation with Quick Connectors	42
Forward-facing Installation with the Seat Belt.....	45

Booster Use

When to Put Your Child in a Booster Seat.....	50
Installation Checklist	53
Converting into a Booster Seat.....	54

General Information

Using the SureLatch Connectors	60
Using the Quick Connectors	61
Adjusting the Headrest.....	62
Adjusting the Recline Position	62
Using the TruTether™ Adjuster.....	63
Installing the Locking Clip.....	64
Removing Seat Pad	66
Installing the Accessories.....	66
Securing Your Child Restraint in Aircraft	68
Installing Child Restraint Rear-facing in Aircraft	68
Installing Child Restraint Forward-facing in Aircraft	71
Care and Cleaning	74
Replacement Parts	76
Limited Warranty	77

Important

Rear-facing

Forward-facing

Booster

General

⚠️WARNING

⚠️ Air Bag Warnings

Rear-facing, Forward-facing, and Booster Use

- **DO NOT** use this child restraint in the front seat of a vehicle equipped with an air bag, unless the air bag has been deactivated. Interaction between a rear-facing restraint and air bags may cause serious injury or death. Air bags may cause serious injury or death to children 12 and under.

If your vehicle has an air bag, refer to your vehicle owner's manual for child restraint installation.

- If the rear seat of your vehicle is equipped with side air bags, refer to the following information for proper usage.

Vehicles built prior to the 2002 model year:

DO NOT use this restraint in a vehicle seating position equipped with a side air bag unless authorized by the vehicle manufacturer.

Model year 2002 and newer vehicles:

Refer to your vehicle owner's manual before placing this restraint in a seating position equipped with a side air bag.

DO NOT place any objects between the restraint and the side air bag, as an expanding air bag may cause the items to strike the child.



⚠️WARNING

General Warnings

Rear-facing, Forward-facing, and Booster Use

- Failure to follow installation instructions can result in the child striking the vehicle's interior during a sudden stop or crash. Serious injury or death may result. These instructions and the instructions in your vehicle owner's manual must be followed carefully. If there is a conflict between the two, the vehicle owner's manual regarding child restraint installation must be followed.
- **NEVER** leave child unattended.
- **DO NOT** use child restraint if it is damaged, broken, or missing parts.
- **DO NOT** use this restraint if it has been involved in a crash. It must be replaced.
- **DO NOT** remove back cover.
- **NEVER** use this child restraint without the headrest installed.

Location Warnings

Rear-facing, Forward-facing, and Booster Use

- **ALWAYS** read and follow exactly the instructions that accompany your vehicle and child restraint.
- According to statistics, children are safer when properly restrained in a rear seating position than in the front seating position. Generally, the center rear position is safest and should be used if available.
- Some child restraints do not fit all vehicles or all seating locations. There are many thousands of combinations of vehicle makes, models, child restraint configurations, vehicle seat belt designs, and seat cushion shapes. The easiest way to determine whether your child restraint is suitable for a particular seating position is to check for a tight installation. If the child restraint cannot be properly installed, **DO NOT** use the child restraint. Consult vehicle owner's manual, try a different seating location, or call Evenflo for further assistance.

⚠WARNING

Location Warnings – cont.

Rear-facing, Forward-facing, and Booster Use

- **ONLY** use this child restraint on **forward-facing vehicle seats**. **DO NOT** use this restraint with vehicle seats that face the rear or side.
- **ONLY** use this child restraint on vehicle seats with backs that lock into place.

Premature Infants

Rear-facing, Forward-facing, and Booster Use

- **DO NOT** use this or any child restraint with a premature infant until after consulting your doctor. Premature infants may have difficulty breathing when in a seated or semi-reclined position. Using additional padding or pillows behind the infant's head or failing to properly recline the child restraint could increase the child's risk of serious injury or death.

Rear-facing Position Warnings

Rear-facing Use Only

- **DO NOT** use this child restraint rear-facing in a vehicle equipped with lap belts that only lock during a sudden stop or crash (emergency locking retractor – ELR). You must use a seating location with a locking seat belt. Check your vehicle owner's manual to see if you have lap belts with ELRs.
- When using this restraint rear-facing, **DO NOT** loosen the vehicle seat belt to provide more leg room, as this will prevent the child restraint from protecting the child.
- Fold-down armrests could pose a hazard to a rear-facing child in certain types of collisions. Consult your vehicle owner's manual before installing any rear-facing child restraint in front of a fold-down armrest.
- **NEVER** turn a child restraint forward-facing with an infant who weighs less than 10 kg (22 lbs) or is less than one year of age. Crash forces may cause serious injury or death.

⚠WARNING

- **NEVER** use *Recline Position #2* or *Recline Position #3* when using this child restraint rear-facing. Use **ONLY** *Recline Position #1*.
- **DO NOT** use the tether strap when the child restraint is in the rear-facing position.
- The headrest on the vehicle seat that the child faces when sitting in the rear-facing mode should be placed in the lowest position. The vehicle seat back that the child faces must be fully padded and free of any hard objects.

Forward-facing Position Warnings

Forward-facing and Booster Use Only

- When using the harness straps to secure a child who is more than 18 kg (40 lbs), **NEVER** place the child restraint in *Recline Position #2*. Use **ONLY** *Recline Position #3*.
- **DO NOT** use *Recline Position #1* or *Recline Position #2* when using this child restraint in Booster Mode. Use **ONLY** *Recline Position #3*.
- Install this child restraint with a vehicle seat belt (**NOT** LATCH connectors) when using the restraint's harness straps to secure a child who weighs more than 21.7 kg (48 lbs).
- If the child weighs more than 29.4 kg (65 lbs) **OR** their shoulders are above the highest harness level, you **MUST** use this child restraint as a booster (p. 50).
- Adjust, or remove, the **vehicle** headrest, **in the seat where the child restraint is to be installed**, so that the back of the child restraint rests against the vehicle seat back.
- The headrest on the vehicle seat in front of the child should be put in its lowest position. The vehicle seat back that the child faces must be fully padded and free of any hard objects.

⚠️WARNING

Booster Seat Position Warnings

Booster Use Only

- **DO NOT** use this booster seat rear-facing.

Seat Belt Warnings

Rear-facing and Forward-facing Use Only

- **DO NOT** use this child restraint if it moves more than 25 mm (1 inch) forward or side-to-side at either rear-facing or forward-facing belt path on the child restraint. Serious injury or death may result from poor installation. If you cannot tightly secure the child restraint, try again or move it to another location.
- **DO NOT** use this child restraint in a seating position with door-mounted seat belts.
- **DO NOT** use this child restraint in a vehicle with seat belts that automatically move along the vehicle frame when the door is opened. These seat belts will not hold a child restraint properly.
- If the vehicle seat belts are not routed and fastened correctly, the child restraint may not protect the child in a crash.
- **DO NOT** allow the vehicle seat belt release button to touch the child restraint. Accidental contact may cause the seat belt to release. If necessary, turn the seat belt release button away from the child restraint or move the child restraint to a different location.
- Failure to adjust the harness or vehicle seat belts snugly around the child may result in the child striking the vehicle's interior during a sudden stop or crash. Serious injury or death may occur.
- Remove locking clip from vehicle seat belt when not used with a child restraint, or the vehicle seat belt will not properly restrain an adult or child. Serious injury or death may occur.



Locking Clip

⚠️WARNING

Booster Mode Only

- To prevent serious injury, use **ONLY** the vehicle's lap **AND** shoulder belt system when restraining a child in this booster seat.
- **DO NOT** use the locking clip when using this child restraint as a booster seat.
- The shoulder belt **MUST** be threaded through the shoulder belt guide (p. 52).
- **DO NOT** use this booster seat if the tops of the child's ears are above the back of the booster seat headrest.
- The shoulder belt **MUST NOT** cross the child's neck **or** fall off the child's shoulder. If you cannot adjust the shoulder belt to **properly lay midway between the child's shoulder and neck AND at or above the shoulder**, try another seating location or do not use the booster seat.



Important



LATCH Warnings

Rear-facing and Forward-facing Modes Only

- This LATCH system is intended to be used **ONLY** as described in these instructions. Serious injury or death may result from misuse.
- In addition to these instructions, read and follow your vehicle owner's manual regarding installation of the child restraint and LATCH. If there is a discrepancy, follow your vehicle owner's manual.
- **ONLY** use for securing child restraint to lower LATCH anchor points.
- **NEVER** attach two LATCH connectors to one vehicle lower anchor point.
- **NEVER** use the vehicle seat belts when using the LATCH system. Using both together can cause slack in a sudden stop or crash.
- When not in use, the LATCH connectors should be securely attached to the D-rings on child restraint seat pad. Keep out of reach of children.

WARNING

LATCH Warnings – cont.

Rear-facing and Forward-facing Modes Only

- **ALWAYS** be sure that the LATCH connectors are fully engaged onto the LATCH anchor points by pulling hard on the LATCH straps. If they are not fully engaged, the LATCH system will not secure your child restraint. Serious injury or death may result.
- **DO NOT** use this child restraint if it moves more than 25 mm (1 inch) forward or side-to-side at either the rear-facing or forward-facing belt path on the child restraint. Serious injury or death may result from poor installation. If you cannot tightly secure the child restraint, try again or move it to another location.

Tether Strap Warnings

Forward-facing and Booster Use Only

- To avoid a strangulation hazard, you **MUST** tightly roll or fold excess or unused tether strap and secure with a rubber band. Attach the tether hook to the storage clip when not in use (p. 13). This will keep an unused tether from hitting someone during a crash.

Additional Warnings

Rear-facing, Forward-facing, and Booster Use

- In hot or sunny weather, **ALWAYS** check the seat, buckle, LATCH hooks, and adjuster for hot areas before placing a child into the child restraint. The child could be burned. Cover the child restraint with a light colored blanket when you leave the vehicle.
- This child restraint must be securely fastened to the vehicle, **even when unoccupied**, using the vehicle seat belts or LATCH connectors. An unsecured child restraint may injure someone if a crash occurs.
- **DO NOT** use the cup holder to store cans or hard cups. Only for use with soft cups (such as styrofoam or paper).

WARNING

- **DO NOT** place any cups that contain hot liquids (such as coffee or tea) in the cup holder.
- **DO NOT** attach additional padding, toys, or other devices not made by Evenflo or described in these instructions to the child restraint. Items not tested with the child restraint could injure the child. Additional pads or pillows may interfere with the function of the harness system, or cause breathing problems if the child's head falls forward, increasing the risk of serious injury or death.
- Failure to follow installation instructions could result in serious injury or death. These instructions and the instructions in your vehicle owner's manual must be followed carefully. If there is a conflict between the two, the vehicle owner's manual regarding child restraint installation must be followed.
- In cold weather, **DO NOT** dress the child in bulky clothing like snowsuits if the child is riding in a child restraint. Bulky coats/snowsuits make it difficult to properly tighten the harness to the child, which may allow the child to be ejected from the restraint during a crash. If necessary, place a blanket over the harnessed child without interfering with the child restraint harness system.

Safe Practices

- **Everyone rides buckled up or the vehicle does not go.** Make no exceptions for adults or children. If someone unbuckles, stop the vehicle. Being firm and consistent from the start will mean fewer discipline problems as children get older. An unrestrained person can be thrown into and injure other passengers.
- Many safety advocates and healthcare professionals recommend that children ride rear facing for as long as possible. See limitations recommended on rear-facing use on the inside front cover.
- **NEVER** try to tend to a crying baby's needs while driving. **NEVER** take a baby out of a child restraint for comforting while the vehicle is moving.
- **DO NOT** allow a child in a vehicle to have objects such as lollipops or ice cream on a stick. The object can injure the child if the vehicle swerves or hits a bump.
- **DO NOT** feed an infant who is riding in a child restraint.
- Put sharp or heavy items in the trunk. Anything loose can be deadly in a crash.

Recall Information for U.S. Customers

- Child restraints could be recalled for safety reasons. You must register this restraint to be reached in a recall. Send your name, address, the restraint's model number, and manufacturing date to:

Evenflo Company, Inc., 1801 Commerce Dr.,
Piqua, OH 45356, or call 1-800-233-5921.

You may also register online at:

www.evenflo.com/registercarseat.

- For recall information call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY:1-800-424-9153), or go to www.NHTSA.gov.

Public Notice for Canadian Customers

- To register your child restraint, return your registration card, call 1-937-773-3971, or register online at www.evenflo.com/registercarseatcanada.
- For recall information, call Transport Canada at 1-800-333-0510 (1-613-993-9851 in Ottawa region) or Evenflo at 1-937-773-3971.

Motor Vehicle/Aircraft Usage

When used with the internal harness and properly installed pursuant to these instructions, this restraint is certified for use only in passenger and multi-purpose passenger motor vehicles, buses, and trucks equipped with Type I or II seat belts and in aircraft.



When used without the internal harness (in booster mode) and properly installed pursuant to these instructions, this restraint is certified for use only in passenger and multi-purpose passenger motor vehicles, buses, and trucks equipped with Type II seat belts. In booster mode, this restraint is NOT certified for aircraft use. A belt-positioning booster requires the use of a lap/shoulder belt system, which is not available on aircraft.

Refer to pages 68 to 73 for instructions on installing your child restraint in aircraft.

LATCH Information

"LATCH" (**L**ower **A**nchors and **T**ethers for **C**hildren) is a system for attaching the child restraint to your vehicle seat. It can be used in place of the seat belts in vehicles with **LATCH** anchors. Refer to your vehicle owner's manual for the locations of **LATCH** anchors. **Note:** Your vehicle owner's manual may refer to this system as "Universal Anchorage System," "Lower Universal Anchorage System," or "ISOFIX."

Symbol Legend



Air Bag Symbol – Alerts you to important information about air bag safety.



LATCH Symbol – Alerts you to important information about LATCH safety.



Tether Anchor Symbol – Alerts you to important information about tether anchor safety.


For future reference, record the **model number** of your child restraint **AND** the **date of manufacture** below (p. 75).

Model Number: _____

Date of Manufacture: _____


Visual Glossary

Your vehicle components may be significantly different than pictured. Consult your owner's manual to help you identify your vehicle components.




IMPORTANT: If your vehicle has **side air bags**, please refer to the warnings on page 2.

Front




Visual Glossary




Important

Back




Securing the Child in the Child Restraint



1. Loosen harness.


Press the harness release button on the front of the seat, then pull up on the harness strap behind the fastened chest clip.



2. Position harness straps.


Unfasten chest clip and place the child in the child restraint. Bring each harness strap over each of the child's shoulders.

IMPORTANT: The baby's back and bottom should be flat against the restraint. If there is a gap, the baby will not be comfortable.



3. Adjust harness straps.


Grasping both harness tabs, slide downward until the harness straps are at the child's shoulders.



4. Buckle the harness.


Insert both buckle tongues into the buckle. **Note:** Pull up on the harness straps to ensure that the buckle tongues are fastened securely.

Securing the Child in the Child Restraint



5. Remove all slack in harness.


Pull upward on the harness straps **near the hips**, as shown, to ensure that all slack is removed.



6. Tighten harness.

Pull the harness adjuster strap to tighten the harness. The harness straps must be snug against the child. A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.

Check the harness straps near the shoulders for slack. You should **NOT** be able to pinch the harness (see illustration). Adjust as needed.



7. Fasten and adjust chest clip.

Snap the two halves of the chest clip together, as shown, and slide to armpit level.

Important

Removing the Child from the Restraint

This page is intentionally blank.





1. Loosen harness straps.

Press the harness release button on the front of the seat while pulling up on the harness strap behind the fastened chest clip.



2. Disconnect chest clip.

Push the release button and pull the chest clip apart.



3. Unbuckle harness.

Press the red button on the buckle and release both buckle tongues.


You may now remove your child.

Using Symphony™ in the Rear-facing Position

Child Requirements

Weight: 2.3 to 18 kg (5 to 40 lbs)

Height: 48 to 94 cm (19 to 37 inches) **AND** the top of child's head is at least 25 mm (1 inch) below the top of the child restraint headrest in either of its two lowest positions.



Rear-facing Installation Checklist

1. Secure child restraint to the vehicle seat.

- ✓ Restraint is securely locked into *Recline Position #1* (p. 62).
- ✓ Locking clip is installed, if necessary (p. 64).
- ✓ The level line is level with ground (p. 23/27).
A towel/small blanket is rolled up and placed beneath the front edge of the base, if necessary.
- ✓ Child restraint is securely installed with one of the following methods using the **rear-facing belt path**:
 - SureLatch Connectors (p. 22)
 - Quick Connectors (p. 26)
 - Vehicle Seat Belts (p. 28)

Note: To determine which type of LATCH connector is on your child restraint, go to page 20.

2. Place the child in the child restraint.

- ✓ The child's back and bottom are flat against the back and bottom surfaces of the child restraint.
- ✓ Top of child's head is at least 25 mm (1 inch) below the top of the child restraint headrest in either of its two lowest positions.

3. Make necessary adjustments.

- ✓ Harness tabs **MUST** be at, or slightly below, shoulder level (p. 14).
- ✓ Headrest is adjusted to either of the bottom two positions closest to the harness tabs (p. 62).

4. Fasten both buckle tongues. Refer to page 14.

5. Position and connect chest clip.

- ✓ Chest clip **MUST** be placed at armpit level (p. 15).

6. Check your work.

- ✓ Harness straps are snug against the child's shoulders, with no slack (p. 15).
- ✓ To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back at the rear-facing belt path.

Rear-facing



To make installation easier, watch the installation video of this child restraint at www.evenflo.com.




Which Type of LATCH Connector is on Your Child Restraint?

In order to properly install your child restraint with the LATCH system, you must first know which type of LATCH connector is present on your child restraint.

- If your child restraint has **SureLATCH Connectors**, begin installation by referring to “Moving SureLatch to the Rear-facing Belt Path,” below.
- If your child restraint has the **Quick Connectors™**, begin installation by referring to page 24, “Moving Quick Connectors to the Rear-facing Belt Path.”

SureLatch Connector



Quick Connector




Moving SureLatch to the Rear-facing Belt Path

To install this child restraint properly in the rear-facing position, the SureLatch assembly must be in the **rear-facing belt path**, as shown below (seat pad has been removed for clarity). If the SureLatch assembly is in the forward-facing belt path (shown below), use the following procedures to move it to the **rear-facing belt path**.


To access the SureLatch assembly, you will first need to:

- Loosen internal harness straps (p. 16);
- Disconnect SureLatch connectors (p. 60);
- Remove seat pad (p. 66).


SureLatch Assembly in Rear-facing Belt Path



SureLatch Assembly in Forward-facing Belt Path




Moving SureLatch to the Rear-facing Belt Path




1. Remove SureLatch connectors from the forward-facing belt path.


Reach through the harness straps and remove each SureLatch connector, one at a time.



2. Place each connector in the rear-facing belt path.



3. Make sure the buckle and crotch strap is positioned in front of the SureLatch assembly, as shown.



Note: Don't forget to install the seat pad before installing the child restraint in your vehicle.


Rear-facing



Rear-facing Installation with SureLatch Connectors


IMPORTANT:

- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use the LATCH system.
- **DO NOT** use the tether strap when the child restraint is in the rear-facing position.



1. Place the child restraint in position.

Adjust the child restraint to the **most** reclined position (*Recline Position #1, p. 62*), then place it on vehicle seat in the rear-facing position, as shown.




2. Attach SureLatch Connectors.

Push a SureLatch connector onto **each** seat anchor.

Note: You may need to vary the angle of the SureLatch connectors, as shown above, to attach to the anchor. Also, make sure the SureLatch assembly is in the rear-facing belt path (p. 20).

IMPORTANT: Make sure both SureLatch connectors are facing upward and the straps are not twisted.




Rear-facing Installation with SureLatch Connectors



3. Increase recline angle, if necessary.

If level line is not parallel to the ground, disconnect SureLatch connectors and place a tightly rolled towel/small blanket beneath the front edge of the child restraint.


Repeat Step 2.





IMPORTANT: Infants may have difficulty breathing when in a sitting position. Make sure they recline enough for their head to lie back comfortably and safely. Failure to properly recline the child restraint could increase the child's risk of serious injury or death.

4. Secure the child restraint.

Using your full weight, push the child restraint firmly into the vehicle seat, as shown, to lock in place.



IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the rear-facing belt path**. If you cannot tightly secure the child restraint, try again or move it to another location.



Note: In some vehicles, you may need to prop up the connector **while** pushing downward on the seat to secure it tightly. Repeat for the other connector.


Moving Quick Connectors to the Rear-facing Belt Path

To install this child restraint properly in the rear-facing position, the Quick Connector LATCH assembly **MUST** be in the **rear-facing belt path**, as shown below (seat pad has been removed for clarity). If the Quick Connector LATCH assembly is in the forward-facing belt path (shown below), use the following procedures to move it to the **rear-facing belt path**.


To access the Quick Connector LATCH assembly, you will first need to:

- Loosen internal harness straps (p. 16);
- Disconnect Quick Connectors (p. 61);
- Remove seat pad (p. 66).

Quick Connector LATCH Assembly in Rear-facing Belt Path




Quick Connector LATCH Assembly in Forward-facing Belt Path




1. Remove Quick Connectors from the forward-facing belt path.

Reach through the harness straps and remove each Quick Connector, one at a time.


Moving Quick Connectors to the Rear-facing Belt Path



2. Place each connector in the rear-facing belt path.



3. Make sure the buckle and crotch strap is positioned in front of the Quick Connector LATCH assembly, as shown.




Note: Don't forget to install the seat pad before installing the child restraint in your vehicle.

Rear-facing

Rear-facing Installation with Quick Connectors


IMPORTANT:

- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use the LATCH system.
- **DO NOT** use the tether strap when the child restraint is in the rear-facing position.



1. Place the child restraint in position.

Adjust the child restraint to the **most** reclined position (*Recline Position #1, p. 62*), then place it on vehicle seat in the rear-facing position, as shown.




2. Attach Quick Connectors.

Push a Quick Connector onto **each** seat anchor.

Note: You may need to vary the angle of the Quick Connectors, as shown above, to attach to the anchor. Also, make sure Quick Connector LATCH assembly is in the rear-facing belt path (p. 24).

IMPORTANT: Make sure both Quick Connectors are facing upward and the straps are not twisted.

Correct



Incorrect




Rear-facing Installation with Quick Connectors

3. Increase recline angle, if necessary.

If level line is not parallel to the ground, disconnect Quick Connectors and place a tightly rolled towel/small blanket beneath the front edge of the child restraint.


Repeat Step 2.



IMPORTANT: Infants may have difficulty breathing when in a sitting position. Make sure they recline enough for their head to lie back comfortably and safely. Failure to properly recline the child restraint could increase the child's risk of serious injury or death.

4. Secure the child restraint.

Using your full weight, push the child restraint firmly into the vehicle seat while pulling up on the LATCH strap to tighten.




IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the rear-facing belt path**. If you cannot tightly secure the child restraint, try again or move it to another location.

Rear-facing

Rear-facing Installation with the Seat Belt

IMPORTANT:


- If you are using the LATCH system to secure the child restraint, **DO NOT** use the vehicle seat belt.
- Before installing this child restraint rear-facing with the vehicle seat belt, you **MUST** move the LATCH assembly to the forward-facing belt path so that it does not interfere with the vehicle seat belt.
- If your child restraint has SureLatch connectors, refer to page 34. If your child restraint has Quick Connectors, refer to page 40. Also, make sure the SureLatch or Quick Connectors are attached to the storage D-rings on the seat pad.
- **DO NOT** use the tether strap when the child restraint is in the rear-facing position.




1. Place the child restraint in position.

Adjust the child restraint to the **most** reclined position (*Recline Position #1, p. 62*), then place it on vehicle seat in the rear-facing position, as shown.

Lap Belt Only



Lap and Shoulder Belt Combination




- 2. Route seat belt through rear-facing belt path.** Unhook the front of the seat pad and move it out of the way. Thread the vehicle seat belt buckle tongue through the rear-facing belt path, as shown.

IMPORTANT: Make sure the buckle/crotch strap is positioned **in front of** the vehicle seat belt (p. 12).


Rear-facing Installation with the Seat Belt

3. Buckle seat belt.




4. Remove all slack from the seat belt.

Using your full weight, push the child restraint firmly onto the vehicle seat while tightening the vehicle seat belt to remove **excess slack**.



5. Install locking clip, if necessary.


You **MUST** use a locking clip if your vehicle has: Lap/shoulder seat belt combination that has a buckle tongue that slides **freely** along the belt **without locking** into place; **OR** Seat belts equipped with an emergency locking retractor (ELR).



Some ELR vehicle belts can be switched so that they lock when tightened. It may not be necessary to use a locking clip in these situations.

Consult your vehicle owner's manual before installing the locking clip.

To see an example of seat belt types and to properly install a locking clip, go to p. 64.




6. Increase recline angle, if necessary.

If the level line is not parallel to the ground, disconnect the seat belt and place a tightly rolled towel/small blanket beneath the front edge of the child restraint.

Repeat Step 2.

IMPORTANT: Infants may have difficulty breathing when in a sitting position. Make sure they recline enough for their head to lie back comfortably and safely. Failure to properly recline the child restraint could increase the child's risk of serious injury or death.



7. Ensure child restraint is secure.

Reconnect the seat pad to the front of the restraint. Try to move the child restraint in all directions.

IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the rear-facing belt path**. If you cannot tightly secure the child restraint, try again or move it to another location.

Using Symphony in the Forward-facing Position

Child Requirements


Weight: 10 to 29.4 kg (22 to 65 lbs)

Height: 71 to 127 cm (28 to 50 inches) **AND** the tops of the child's ears are below the top of the child restraint headrest.

Age: At least one year old

IMPORTANT

You must use the top anchorage (tether) strap when securing a child in this child restraint forward-facing with the harness straps. Using the tether strap will improve the stability of this child restraint and may reduce the risk of injury.



⚠ WARNING

If the child weighs more than 29.4 kg (65 lbs) **OR** their shoulders are above the highest harness level, you **MUST** use this child restraint as a booster seat.

Forward-facing Installation Checklist

1. Secure child restraint to the vehicle seat.

- ✓ Restraint is securely locked into *Recline Position #2* or *#3* (p. 62).
- ✓ Locking clip is installed, if necessary (p. 64).
- ✓ **If the child weighs 21.7 kg (48 lbs) or less**, the child restraint is securely installed with one of the following methods through the **forward-facing belt path**:
 - SureLatch Connectors (p. 34)
 - Quick Connectors (p. 40)
 - Vehicle seat belt (p. 45)

Note: To determine which type of LATCH connector is on your child restraint, go to page 34.

- ✓ **If the child weighs more than 21.7 kg (48 lbs)**, the child restraint is securely installed with the vehicle seat belt (not LATCH) through the **forward-facing belt path** (p. 45).
- ✓ Tether strap is attached and tightened (p. 39, 44, or 48).

2. Place the child in the child restraint.

- ✓ The child's back and bottom are flat against the back and bottom surfaces of the child restraint.
- ✓ The tops of the child's ears **MUST** be below the top of the child restraint headrest.

3. Make necessary adjustments.

- ✓ Harness tabs **MUST** be at shoulder level (p. 14).
- ✓ Headrest is adjusted so that its bottom is nearest to the harness tabs (p. 62).

4. Fasten both buckle tongues. Refer to page 14.

5. Position and connect chest clip.

- ✓ Chest clip **MUST** be at armpit level (p. 15).

6. Check your work.

- ✓ Harness straps are snug against the child's shoulders, with no slack (p. 15).
- ✓ To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from **side-to-side** or from **front-to-back** at the forward-facing belt path.




Which Type of LATCH Connector Is on Your Child Restraint?

In order to properly install your child restraint with the LATCH system, you must first know which type of LATCH connector is present on your child restraint.

- If your child restraint has **SureLatch Connectors**, begin installation by referring to “Moving SureLatch to the Forward-facing Belt Path,” below.
- If your child restraint has the **Quick Connectors**, begin installation by referring to page 40, “Moving Quick Connectors to the Forward-facing Belt Path.”

SureLatch Connector



Quick Connector




Moving SureLatch to the Forward-facing Belt Path

To install this child restraint properly in the forward-facing position, the SureLatch assembly **MUST** be in the **forward-facing belt path**, as shown below (seat pad has been removed for clarity). If the SureLatch assembly is in the rear-facing belt path (shown below), use the following procedures to move it to the **forward-facing belt path**.


To access the SureLatch assembly, you will first need to:

- Loosen internal harness straps (p. 16);
- Disconnect SureLatch connectors (p. 60);
- Remove seat pad (p. 66).


SureLatch Assembly in Forward-facing Belt Path




SureLatch Assembly in Rear-facing Belt Path



Moving SureLatch to the Forward-facing Belt Path




- 1. Remove one SureLatch connector from the rear-facing belt path.**



- 2. Place the connector in the forward-facing belt path.**

Pull the harness strap out of the way and insert the connector, **behind** the straps, into the forward-facing belt path opening, as shown.

Repeat on the other side.



- 3. Make sure the SureLatch assembly does not interfere with the internal harness straps.**

Note: Don't forget to install the seat pad before installing the child restraint in your vehicle.


Forward-facing




Forward-facing Installation with SureLatch Connectors

IMPORTANT:

- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use SureLatch connectors.
- Install this child restraint with the vehicle seat belt (**NOT** LATCH connectors) if the child weighs **more** than 21.7 kg (48 lbs).
- Some vehicle manufacturers have lower maximum weight ratings for LATCH anchors. Consult your vehicle owner's manual, or call the vehicle manufacturer, to confirm the limits on your vehicle's LATCH anchors.



1. Disconnect the tether hook from the back of the child restraint.




2. Place the child restraint in position.

Make sure child restraint is in **Recline Position #2** or **#3** (p. 62).

Set child restraint on vehicle seat in the **forward-facing** position, as shown. Lay the tether strap over the back of the vehicle seat.

IMPORTANT: NEVER use **Recline Position #1** for forward-facing, AND **NEVER** use **Recline Position #2** with children who weigh more than 18 kg (40 lbs).

Forward-facing Installation with SureLatch Connectors




3. Attach SureLatch Connectors.

Push a SureLatch connector onto **each** seat anchor.

Note: You may need to *vary the angle* of the SureLatch connectors, as shown above, to attach to the anchor.


Also, make sure the SureLatch assembly is in the forward-facing belt path (p. 34).

IMPORTANT: Make sure both SureLatch connectors are facing upward and the straps are not twisted.



Forward-facing


Forward-facing Installation with SureLatch Connectors




4. Secure the child restraint.

Using your full weight, push the child restraint firmly into the vehicle seat, as shown, to set it in place.


IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the forward-facing belt path**. If you cannot tightly secure the child restraint, try again or move it to another location.



Note: In some vehicles, you may need to prop up the connector **while** pushing downward on the seat to secure it tightly. Repeat for the other connector.



Forward-facing Installation with SureLatch Connectors



5. Connect and tighten tether strap.


Connect the tether hook to the anchor behind the vehicle seat, as shown. Pull the strap and tighten the tether securely.

IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink.

Notice

Your child restraint is equipped with one of two types of tether adjusters: standard (shown above) or the TruTether™ (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 63 for information about proper tightening.

TruTether Adjuster




Moving Quick Connectors to the Forward-facing Belt Path

To install this child restraint properly in the forward-facing position, the Quick Connector LATCH assembly **MUST** be in the **forward-facing belt path**, as shown below (seat pad has been removed for clarity). If the Quick Connector LATCH assembly is in the rear-facing belt path (shown below), use the following procedures to move it to the **forward-facing belt path**.



To access the Quick Connector LATCH assembly, you will first need to:

- Loosen internal harness straps (p. 16);
- Disconnect Quick Connectors (p. 61);
- Remove seat pad (p. 66).

Quick Connector LATCH Assembly in Forward-facing Belt Path




Quick Connector LATCH Assembly in Rear-facing Belt Path



1. Remove one Quick Connector from the rear-facing belt path.


Moving Quick Connectors to the Forward-facing Belt Path



2. Place the connector in the forward-facing belt path.

Pull the harness strap out of the way and insert the connector, **behind** the straps, into the forward-facing belt path opening, as shown.

Repeat on the other side.



3. Make sure the Quick Connector LATCH assembly does not interfere with the internal harness straps.


Note: Don't forget to install the seat pad before installing the child restraint in your vehicle.

Forward-facing


Forward-facing Installation with Quick Connectors

IMPORTANT:

- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use the Quick Connectors.
- Install this child restraint with the vehicle seat belt (**NOT** LATCH connectors) if the child weighs **more** than 21.7 kg (48 lbs).
- Some vehicle manufacturers have lower maximum weight ratings for LATCH anchors. Consult your vehicle owner's manual, or call the vehicle manufacturer, to confirm the limits on your vehicle's LATCH anchors.



1. Disconnect tether hook from the back of the child restraint.




2. Place the child restraint in position.

Make sure child restraint is in *Recline Position #2* or #3 (p. 62).

Set child restraint on the vehicle seat in the **forward-facing** position, as shown. Lay the tether strap over the back of the vehicle seat.

IMPORTANT: NEVER use *Recline Position #1* for forward-facing, **AND NEVER** use *Recline Position #2* with children who weigh more than 18 kg (40 lbs).

Forward-facing Installation with Quick Connectors




3. Attach Quick Connectors.

Push a Quick Connector onto **each** seat anchor.

Note: You may need to vary the *angle* of the Quick Connectors, as shown above, to attach to the anchor. Also, make sure the Quick Connector LATCH assembly is in the forward-facing belt path (p. 40).

IMPORTANT: Make sure both Quick Connectors are facing upward and the straps are not twisted.

Correct



Incorrect



Forward-facing Installation with Quick Connectors

4. Secure the child restraint.


Using your full weight, push the child restraint firmly into the vehicle seat while pulling up on the LATCH strap to tighten.

Forward-facing
Belt Path

IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or

from front-to-back **at the forward-facing belt path.**

If you cannot tightly secure the child restraint, try again or move it to another location.



5. Connect and tighten tether strap.


Connect the tether hook to the anchor behind the vehicle seat, as shown. Pull the strap and tighten the tether securely.

IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink.

Notice

Your child restraint is equipped with one of two types of tether adjusters: standard (shown above) or the TruTether (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 63 for information about proper tightening.


TruTether Adjuster




Forward-facing Installation with Seat Belt

IMPORTANT:

- If you are using the LATCH system to secure the child restraint, **DO NOT** use the vehicle seat belt.
- Before installing this child restraint **forward-facing with the vehicle seat belt**, you **MUST** move the LATCH assembly to the **rear-facing belt path** so that it does not interfere with the vehicle seat belt.
- If your child restraint has SureLatch connectors, refer to page 20. If your child restraint has Quick Connectors, refer to page 24. Also, make sure the SureLatch or Quick Connectors are attached to the storage D-rings on the seat pad.



1. Disconnect tether hook from the back of the child restraint.




2. Place the child restraint in position.

Make sure child restraint is in **Recline Position #2 or #3** (p. 62).

Set child restraint on vehicle seat in the **forward-facing** position, as shown. Lay the tether strap over the back of the vehicle seat.

IMPORTANT: NEVER use **Recline Position #1** for forward-facing, **AND NEVER** use **Recline Position #2** with children who weigh more than 18 kg (40 lbs).


Forward-facing Installation with Seat Belt



3. Route seat belt through forward-facing belt path.

Move the harness out of the way and raise the access flap. Route the seat belt buckle tongue through the forward-facing belt path, as shown.

4. Buckle seat belt.



Forward-facing Installation with Seat Belt




5. Remove all slack from the seat belt.

Using your full weight, push the child restraint firmly into the vehicle seat while tightening seat belt to remove **excess** slack.

6. Install locking clip, if necessary.

You **MUST** use a locking clip if your vehicle has: Lap/shoulder seat belt combination that has a buckle tongue that slides **freely** along the belt **without locking** into place; **OR** Seat belts equipped with an emergency locking retractor (ELR).




Some ELR vehicle belts can be switched so that they lock when tightened. It may not be necessary to use a locking clip in these situations.

Consult your vehicle owner's manual before installing the locking clip.

To see an example of seat belt types and to properly install a locking clip, go to p. 64.


Forward-facing Installation with Seat Belt



7. Ensure child restraint is secure.

Hold the child restraint near the vehicle belt path, as shown, and try to move it in all directions.

IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the vehicle belt path**. If you cannot tightly secure the child restraint, try again or move it to another location.



8. Connect and tighten tether strap.

Connect the tether hook to the anchor behind the vehicle seat, as shown. Pull the strap and tighten the tether securely.


IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink.

Forward-facing Installation with Seat Belt

Notice

Your child restraint is equipped with one of two types of tether adjusters: standard (shown above) or the TruTether (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 63 for information about proper tightening.

TruTether Adjuster



When to Put Your Child in a Booster Seat

Booster seats raise the child up and help to position the vehicle lap and shoulder belt correctly. When the child is **properly restrained** in a booster seat, his/her risk of injury in all types of crashes is reduced, as the lap and shoulder belt provides excellent restraint of both the upper and lower torsos.

It is important for the child to sit properly within the vehicle seat belts. When the vehicle belt is buckled, the lap belt should be low on the hips, just touching the thighs, and the shoulder belt should lie across the middle of the shoulder. If the child leans out or moves the belt behind the back or places it under the arm, it **will not provide the intended restraint.**

There are a number of things to consider when deciding whether a child is ready to sit in a booster seat, including: the weight and height ratings on his/her current child seat, the child's own weight and height, his/her maturity, and the seating positions available in your vehicle.

How is a booster seat used?


Using a booster seat is very similar to buckling yourself into the vehicle:

- Read the instruction manuals for both the booster seat and the vehicle before you start.
- Put the booster in the back seat in a location with a lap and shoulder belt. **Never use a booster with only a lap belt**, as this could cause serious injuries.
- After the child is in the booster, pull the lap and shoulder belt across him/her and buckle it.
- Check that the shoulder belt lies across the middle of the shoulder and that the lap belt is low on the hips, just touching the thighs.

How can you tell if a child is ready to transition to a booster seat?

You should consider using a booster seat if the following conditions apply:

- The child is mature enough to sit in the booster seat and not put the belts under his/her arm or behind his/her back.
- The child is approaching the weight or height limit of the child restraint he/she is currently using. (Even children who have not outgrown their toddler seat can benefit from the use of a booster seat, if it is used properly.)
- If you have a vehicle that does not have a tether anchorage but has lap/shoulder belts available in the back seat, a booster seat may provide better protection than an internal harness seat without the tether.



Using Symphony as a Booster Seat


Child Requirements

Weight: 18 to 49.8 kg (40 to 110 lbs)

Height: Child is 110 to 145 cm (43.3 to 57 inches)

Tops of child's ears are below the top of the child restraint headrest.

Age: At least four years old



IMPORTANT

Always secure the booster seat with the LATCH connectors or vehicle seat belt when not occupied. An unsecured booster seat can fly into and injure other occupants in the event of a crash.

Booster Installation Checklist

1. Convert child restraint to booster seat.

See "Converting into a Booster Seat," p. 54.

2. Secure booster seat to the vehicle seat.

Make sure the bottom and back of the booster seat are touching vehicle seat and back.

IMPORTANT: You may use the tether strap and LATCH connectors to secure this booster seat to the vehicle seat **ONLY** if the position of the booster seat in the vehicle and/or the position of the vehicle seat belt over the child are **not affected**.

3. Place the child in the booster seat.

- ✓ Make sure the booster seat is securely locked into **Recline Position #3** (p. 62).
- ✓ Make sure the child's back and bottom are flat against the back and bottom surfaces of the booster seat.

4. Adjust headrest for proper shoulder belt fit.

The shoulder belt **MUST** cross midway between the child's shoulder and neck, as shown.

5. Secure child and booster seat to vehicle seat.

Stretch the lap/shoulder belt across the child and fasten the buckle. Make certain the shoulder belt is threaded through the shoulder belt guide, as shown.

6. Check your work.


Make sure the lap belt is stretched low and snug across the child's hips, within the lower belt guides, and fastened into the buckle. The shoulder belt must cross the child midway between his/her shoulder and neck.



⚠ WARNING

The shoulder belt **MUST NOT** cross the child's neck or fall off the child's shoulder. If you cannot adjust the shoulder belt to properly lay midway between the child's shoulder and neck **AND** at or above the shoulder, try another seating location or do not use the booster seat.


Converting into a Booster Seat



1. Remove the seat pad (p. 66).

Adjust the headrest to its uppermost position (p. 62).


Pull the LATCH connectors from the forward-facing belt path and place them in the seat, as shown.



2. Loosen harness.




Press the harness release button and pull the harness straps outward.

Converting into a Booster Seat



3. Push the chest clip and buckle tongues through the forward-facing belt path.

Buckle the chest clip behind the child restraint, as shown below.



4. Conceal harness tabs.


Tuck harness tabs completely into adjustment slots, as shown.

Note: If the harness tabs are not tucked completely into the slots, they will press uncomfortably against your child's back.

Converting into a Booster Seat



5. Tighten harness straps.

Pull harness adjustment strap until harness straps are tight.



6. Insert LATCH connectors.



Insert both LATCH connectors through the forward-facing belt path.




Converting into a Booster Seat

7. Remove the crotch strap.


Place the child restraint in *Recline Position #1* (p. 62), then lay it on its back. Locate the crotch strap anchor on the bottom.





Unclip the anchor, push it through the seat, and remove, as shown.



Insert the crotch strap anchor back into the opening from the bottom of the child restraint.



Pull the anchor completely through the seat and arrange it so it lies flat, as shown.





8. Install the seat pad.

Fasten each LATCH connector to its D-ring for storage (pages 60 and 61).


IMPORTANT

*Make sure the child restraint is adjusted to **Recline Position #3** (p. 62) and the headrest is adjusted for proper shoulder belt fit (p. 62).*

Your child restraint is now in booster mode and ready for a child who weighs 18 to 49.8 kg (40 to 110 lbs), who is 110 to 145 cm (43.3 to 57 inches) tall, who is at least four years old, and whose ears are below the top of the child restraint headrest.


General Information

Using the SureLatch Connectors




To remove the SureLatch connector from a LATCH anchor or its storage D-ring, press the Release Button.

When the SureLatch assembly is in the **forward-facing belt path**, store each SureLatch connector by snapping it onto a **forward** D-ring.



When the SureLatch assembly is in the **rear-facing belt path**, store each SureLatch connector by snapping it onto a **rear** D-ring.




Using the Quick Connectors




To remove the Quick Connector from a LATCH anchor or its storage D-ring, pull the Release Strap.

When the Quick Connector LATCH assembly is in the **forward-facing belt path**, store each Quick Connector by snapping it onto a D-ring, as shown.




When the Quick Connector LATCH assembly is in the **rear-facing belt path**, store each Quick Connector by snapping it onto a D-ring, as shown.



Adjusting the Headrest


Headrest Adjust Lever



To adjust, squeeze the headrest adjust lever, as shown, while sliding the headrest up or down to the desired position.

Adjusting the Recline Position

This child restraint can be adjusted into three positions.



Squeeze the recline lever at the bottom of the child restraint, as shown, and select the desired recline position.

IMPORTANT: After adjusting the recline position, rock the child restraint back and forth to make sure it is securely locked in the desired position.

CORRECT RECLINE POSITIONING

- In rear-facing position: Use **Recline Position #1 ONLY**.
- In forward-facing position when child is secured with harness straps: Use **Recline Position #2** for children who weigh 10 to 18 kg (22 to 40 lbs); use **Recline Position #3** for children who weigh 10 to 29.4 kg (22 to 65 lbs).
- In booster mode: Use **Recline Position #3 ONLY**.



Using the TruTether Adjuster

Not available on all models.

Tether straps equipped with the TruTether adjuster attach to vehicle tether anchor brackets exactly the same as tether straps with standard tether adjusters. TruTether adjusters, however, are equipped with a Tightness Indicator that shows, at a glance, whether the tether strap is properly tightened. When the Tightness Indicator Display is "green," the tether strap is tight enough.

TruTether Adjuster

Tightness Indicator Display




Connect the tether hook to the anchor behind the vehicle seat, as shown.

Pull the strap until you see green in the tightness indicator display. Once it has turned green, you have removed all slack, and the tether strap is adequately tightened. Be sure to check it periodically to make sure the indicator is still green. If no green is showing, pull the strap until it is.

Installing the Locking Clip

To view a video about installing a locking clip, go to www.evenflo.com.



Use the locking clip with:

- Lap/shoulder seat belt combinations that have a buckle tongue that slides freely along the belt without locking into place;

OR

- Seat belts equipped with an emergency locking retractor (ELR). Some ELR vehicle belts can be switched so that they lock when tightened. **It may not be necessary to use a locking clip in these situations.**


Consult your vehicle owner's manual before installing the locking clip.

⚠ WARNING

Locking Clip




- Remove locking clip from vehicle seat belt when not used with a child restraint, or the vehicle seat belt will not properly restrain an adult or child. Serious injury could occur.
- **DO NOT** use the locking clip in booster mode.




1. Using your full weight, press down on the child restraint as you tighten the seat belt.


Installing the Locking Clip



2. Hold the lap/shoulder belts together just behind the free sliding buckle tongue while you unfasten the seat belt.



3. While holding the belts and buckle tongue, thread the locking clip onto the seat belt and slide it into place. **Note:** Locking clip must be placed within 13 mm (0.5 inch) of seat belt buckle.




4. Buckle the seat belt with the locking clip in place.

Return to the installation procedure:

- Rear-facing installation – Step 6, page 30
- Forward-facing installation – Step 7, page 48

Removing Seat Pad



1. Disconnect all LATCH connectors from D-rings on seat pad.
2. Open "EZ Off" pad enclosure.
3. Disconnect all seat pad hooks. Remove the seat pad.

Installing the Accessories


⚠ WARNING

- Use the fold-down cup holder with the child restraint in the forward-facing position **ONLY**.
- **DO NOT** use the cup holder to store bottles or hard containers. Only for use with soft cups (such as styrofoam or paper).
- **DO NOT** place any cups that contain hot liquids (such as coffee or tea) in the cup holder.
- **DO NOT** attach any other item to this child restraint unless it has been certified for use with this specific child restraint.



To install the fold-down cup holder on either side of the restraint, move seat pad out of the way and install on the side, as shown.

To use, flip it open.



Installing the Accessories

⚠ WARNING

Use the Body Pillow and Infant Head Support (head pillow) with the child restraint in the rear-facing position **ONLY**.



The optional Body Pillow, when placed in the restraint, as shown, helps support your child.

IMPORTANT:

- The head pillow should lie flat against the seat back, as shown. Be sure to cut off the plastic attachment between the head support and the seat pad. Small parts may be a choking hazard.
- Support the child's head. Infants may have difficulty breathing when in a sitting position. Using additional padding or pillows behind the infant's head or failing to properly recline the child restraint could increase the child's risk of serious injury or death.

Securing Your Child Restraint in Aircraft

The Federal Aviation Administration (FAA) recommends that you secure your child for air travel in an appropriate child restraint based on your child's weight and size. Turbulence can happen with little or no warning. When turbulence occurs, **the safest place for your child is in a properly installed child restraint, not in an adult's lap or on the aircraft seat with its seat belt.** Keeping your child in a child restraint during the flight will help ensure your family arrives safely at your destination.

The FAA recommends that a child weighing:*

- more than 18 kg (40 lbs) use an aircraft seat belt;
- less than 9 kg (20 lbs) use a rear-facing child restraint; and
- from 9 to 18 kg (20 to 40 lbs) use a forward-facing child restraint.


*** Please note that these FAA recommendations may vary from those applicable to the use of your child restraint in a motor vehicle.**

IMPORTANT

You must use the internal harness when installing the child restraint in aircraft.

Installing Child Restraint Rear-facing in Aircraft


IMPORTANT: Before installing the child restraint, make sure the **aircraft seat is in a fully upright position.**



1. Place the child restraint in position.

Adjust the child restraint to its **most** reclined position (*Recline Position #1, p. 62*), then place it on the aircraft seat rear-facing, as shown.


Installing Child Restraint Rear-facing in Aircraft



2. Route aircraft seat belt through rear-facing belt path.


Unhook the front of the seat pad of the child restraint and move it out of the way. Route the aircraft seat belt buckle through the rear-facing belt path opening on one side and continue through the opening on the opposite side of the child restraint, as shown.

IMPORTANT: For aircraft use **ONLY**, make sure the aircraft seat belt is positioned **in front of** the buckle/crotch strap, as shown above.



3. Fasten the aircraft seat belt.

Installing Child Restraint Rear-facing in Aircraft



4. Remove all slack from the aircraft seat belt.

The aircraft seat belt must be as tight as possible. Using your full weight, push the child restraint firmly onto the aircraft seat while pulling on the seat belt to tighten. Route the excess seat belt strap through the rear-facing belt path opening.




5. Check your work.

Reconnect the seat pad to the front of the child restraint. Try to move the child restraint in all directions. If you can move the restraint more than 25 mm (1 inch) forward or side-to-side at the rear-facing belt path, the aircraft seat belt is not tight enough, and you **MUST** install again until the seat belt is tight.


Installing Child Restraint Forward-facing in Aircraft

IMPORTANT: Before installing the child restraint, make sure the **aircraft seat is in a fully upright position**.



1. Place the child restraint in position.


Adjust the child restraint to its **most** upright position (*Recline Position #3, p. 62*), then place it on the aircraft seat forward-facing, as shown above.




2. Route aircraft seat belt through forward-facing belt path.

Move the child restraint's harness out of the way and raise the access flap. Route the aircraft seat belt buckle through the forward-facing belt path opening on one side, as shown, and continue through the opening on the opposite side of the child restraint, as shown above.

Installing Child Restraint Forward-facing in Aircraft



3. Fasten the aircraft seat belt.




4. Remove all slack from the aircraft seat belt.

The aircraft seat belt must be as tight as possible. Using your full weight, push the child restraint firmly onto the aircraft seat while pulling on the aircraft seat belt to tighten. Route the excess seat belt strap through the forward-facing belt path opening.

Note: Because of the fixed length of aircraft seat belts, the belt buckle could be behind the child's back after tightening the belt. For your child's comfort, Evenflo recommends cushioning the child's back by placing a small pillow or folded-up blanket, or a folded-up jacket, over the belt buckle.

Installing Child Restraint Forward-facing in Aircraft



5. Check your work.

Hold the child restraint near the forward-facing belt path, as shown, and try to move it in all directions. If you can move the child restraint more than 25 mm (1 inch) forward or side-to-side at the belt path, the aircraft seat belt is not tight enough, and you **MUST** install again until the aircraft seat belt is tight.

Care and Cleaning

- **DO NOT** lubricate or immerse in water the SureLatch connectors, the buckle, or any other part of this child restraint, unless rinsing is permitted, as stated on the back of the buckle for your restraint.
- Plastic and metal parts may be wiped clean with mild soap and water and dried with a soft cloth. Do not use abrasive cleaners or solvents.
- Take care not to damage any labels.
- The harness can be wiped clean with mild soap and water. Allow harness to air dry.
- Machine wash the seat pad separately in cold water, delicate cycle. Tumble dry 10 to 15 minutes on low heat.
- **NEVER** use child restraint without the seat pad.

Tip!

To help protect the vehicle upholstery, place a towel beneath and behind the child restraint.

Proper Disposal of This Child Restraint


At the end of this child restraint's useful life, Evenflo encourages you to dispose of it properly. Most of the components in this child restraint are recyclable.

1. Remove all fabric and padding.
2. Remove all screws and disassemble the restraint.
3. Recycle all plastic/foam parts and discard the rest.

If your local recycling center won't accept the padding, you may dispose of it in the landfill.

Note: Evenflo uses recycled materials in the manufacturing process whenever possible but never for components that are critical for safety.

To prevent injury due to hidden damage, lost instructions, outdated technology, etc., discontinue use of this restraint after eight years or if it has been involved in a crash.



After thoroughly reading and following these instructions, store them in the slots provided on the back of the child restraint, as shown.


Replacement Parts

Not available on all models.


You can order replacement parts online at www.evenflo.com or call Evenflo. When you contact us, please have the product model number and date of manufacture (found on the back of the child restraint).



Locking
Clip




Cup
Holder




Upper Seat
Foam




Body
Pillow




Lower Seat
Foam



Tether
Extender



Headrest
Pad



Headrest



SureLatch Assembly



Seat
Pad



Quick Connector LATCH
Assembly

Limited Warranty

For a period of 90 days from the original purchase of this Product, Evenflo warrants to the original end user ("Purchaser") this Product (including any accessories) against defects in material or workmanship. Evenflo's sole obligation under this express limited warranty shall be, at Evenflo's option, to repair or replace any Product that is determined to be defective by Evenflo and determined to be covered by this warranty.

Repair or replacement as provided under this warranty is the exclusive remedy of the Purchaser. Proof of purchase in the form of a receipted invoice or bill of sale evidencing that the Product is within the warranty period must be presented to obtain warranty service. This express limited warranty is extended by Evenflo ONLY to the original Purchaser of the Product and is not assignable or transferable to subsequent purchasers or end users of the Product. For warranty service, contact Evenflo's ParentLink Consumer Resource Center at www.evenflo.com.

EXCEPT TO THE EXTENT PROHIBITED BY APPLICABLE LAW, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS HEREBY DISCLAIMED. EVENFLO SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL, SPECIAL OR PUNITIVE DAMAGES OF ANY KIND FOR BREACH OF THE EXPRESS LIMITED WARRANTY ON THIS PRODUCT, OR ANY WARRANTY IMPLIED BY OPERATION OF LAW. OTHER THAN THE EXPRESS LIMITED WARRANTY SET FORTH ABOVE, THERE ARE NO OTHER WARRANTIES THAT ACCOMPANY THIS PRODUCT AND ANY ORAL, WRITTEN OR ANY OTHER EXPRESS REPRESENTATION OF ANY KIND IS HEREBY DISCLAIMED.

ParentLink®

answers. advice. affirmation.™

- **USA:** 1-800-233-5921, 8 AM to 5 PM E.T.
- **Canada:** 1-937-773-3971
- **México:** 01-800-706-12-00

ParentLink®

answers. advice. affirmation.™

- **USA:** 1-800-233-5921, 8 AM to 5 PM E.T.
- **Canada:** 1-937-773-3971
- **México:** 01-800-706-12-00



APPROVAL SHEET

Responsibility	Signature
Design Engineer	
Engineering Manager	
Director Engineering	
Assoc. Product Manager	
Product Manager	
Product Integrity Engineer	
Director Product Integrity	

Piqua Lab Manager	
Legal	
Product Claims	
ParentLink	
TM Review	